



FX 500

Higher Performance
Enhanced Connectivity

The FX 500 FleetBroadband terminal is the latest-generation maritime communication systems operating on the Inmarsat FleetBroadband Satellite System. It is compact and easy to install. The FX 500 terminal is Inmarsat approved for use with XpressLink.

Using Inmarsat's most advanced commercial communication satellites, the FX 500 FleetBroadband terminal provides simultaneous access to clear digital voice or fax, high-speed Standard IP (for email, FTP, web browsing etc.) and Streaming IP data (for real-time streaming video etc.) and SMS. It makes it easier for the Captain to download the latest weather and navigational charts while the crew members can call, talk, send and receive text messages and email around the world. Moreover there will be no noticeable degradation of data bandwidth when the terminal is at the edge of satellite coverage unlike other classes of FleetBroadband terminals.

The FX 500 FleetBroadband terminal offers data speeds of up to 432kbps with many value-added features:

- Firewall
- Fleet Tracking Capability with Geo-fencing - up to 10 polygon geo-fence areas can be configured
- Wi-Fi (802.11b/g)
- Push To Talk (PTT)
- Forced Dialing – SAC Configuration Control
- Restricted Dialing (for crew calling)
- Handset Call Priority (allows the Captain to pre-empt the active CS call)
- Remote Access (for configuration and diagnostics)
- Radio Silence (radio transmission on/off) Control
- External Ringer Control
- Framed-Routing Network Management (includes supporting Inmarsat XpressLink)
- Remote Management (using SMS/AT commands)
- Backup / Restore of Configuration Settings
- SIM Lock based on IMSI/APN
- Multilingual WebConsole (English, Spanish, Dutch, Japanese, Korean, Simplified Chinese and Traditional Chinese)
- Multi-User WebConsole access with configurable access rights
- Time/Volume limited data sessions (to avoid bill shock)
- PPPoE
- MAC Filtering (with whitelist/blacklist)
- NAT and NAT (Port Forwarding)
- NMEA 0183 Continuous GPS Output
- SMS with option to append GPS position

The FX 500 is a high performance satellite communication terminal with the salient features:

- 3-Axis Stabilised Antenna including ATC-Resilience, Extended L-Band and IP56 Protection capability.
- No Fuses – Uses Intelligent Circuit Breaker protection
- Primary Handset with IP66 Environmental Protection (for voice, SMS & terminal configuration)

The FX 500 includes a primary handset with a large colour LCD display and mobile phone type keys for making/receiving phone calls, making selective terminal configuration changes, sending and receiving SMS messages, including larger SMS content of greater than 160 characters as multipart or segmented messages. This feature is popular for the Captain and the crew members who are used to texting from their mobile phones while on shore.

The FX 500 can act as a WAN connection to any onboard computer network (LAN) by simply connecting the unit to the onboard LAN and making all the devices attached to the LAN accessible to the Internet. The MAC Filtering feature provides a strong security option by providing access rights only to selected devices based on their MAC addresses. A Firewall option complements the security options by not only blocking unauthorized remote access but also blocks unwanted data traffic thus saving unwanted air-time costs.

The Network Management feature supporting Direct Mode (one-to-one), Shared Mode (multi-user) and a DMZ mode makes it powerful enough to configure the FX 500 with the attached devices in many different combinations of network configurations.

The FleetBroadband terminal has a continuous GPS output feature which allows GPS data to be sent out via the RS232 port in standard NMEA 0183 format. With the built-in GPS module, the FX 500 is able to provide accurate position information to onboard systems such as plotters and depth sounders, with a configurable baud-rate setting.

With the standard built-in Wi-Fi feature, the web-based user interface can be accessed via any web browser including Wi-Fi-enabled Smartphones such as BlackBerrys, iPhones, Android Phones, iPads, and PDAs via the FX 500's secure Wi-Fi (WLAN). The Wi-Fi connection also offers a wireless Push-to-Talk (PTT) service to Smartphone users using free PTT applications such as Zello, without having to add any additional hardware to the terminal (unlike other PTT solutions that require expensive add-on hardware).

Technical Specifications

Inmarsat FleetBroadband Type Approval
 Inmarsat XpressLink Certified
 Compliant to R&TTE, IEC60945:2002, RoHS
 Certification Mark : FCC, CE, Industry Canada
 Wi-Fi Compliant IEEE802.11b/g
 Green Passport

Frequency Band

Transmit: 1626.5 ~ 1660.5 and 1668.0 ~ 1675.0 MHz
 Receive: 1518.0 ~ 1559.0 MHz

Recommended Antenna Cable

Cable loss: 10dB at 1.6GHz and 1 ohm DC loop resistance

BDU Interfaces

Power On/Off Switch
 DC Power Input Socket
 Antenna Connector (N-Type)
 Status Indicator LEDs (3)
 SIM Card Slot
 GPS Output (NMEA 0183)
 Primary Handset Connector
 4 RJ45 Ethernet Connectors (including 2 x Power over Ethernet (PoE) ports)
 2 RJ11 Connectors for Analog Phone and G3 Fax
 Built-in WLAN 802.11b/g
 Resettable Circuit Breaker
 Safe Mode Switch
 I/O Connector for Radio Silence, External Ringer, etc
 Grounding Stud

Communication Services

Standard Voice : 4 kbps circuit switched (AMBE+2 codec)
 Standard IP : Up to 432 kbps
 Streaming IP : 8k, 16k, 32k, 64k, 128k, 176k and 256 kbps
 Fax : G3 FAX (using 3.1kHz audio channel)
 Short Messaging Service (SMS) : Up to 160 characters (3G standard)
 Larger SMS content : supported as multipart or segmented SMS (> 160 characters)

Network Management Functions

Shared Mode: NAT/NAPT enabled, Multi-User access with DHCP
 DMZ Mode: NAT enabled for end-to-end dedicated TE access
 Direct Mode: NAT disabled for end-to-end dedicated TE access

Environmental Conditions

Operating Temperature : -25 to +55°C
 Storage Temperature : -40 to +80°C
 Operating Humidity : 95% non-condensing at +40°C
 ADU Ingress Rating : IP56
 BDU Ingress Rating : IP31

Ship Motion

Roll : ±30° / 4s period, max 0.7g tan.
 Pitch : ±15° / 3s period, max 0.6g tan.
 Yaw : ±10° / 5s period, max 0.3g tan.
 Turning Rate : ± 36°/s, acc. max 12°/s²
 Surge : ±0.5g
 Sway : ±0.5g
 Heave : ±0.7g
 Headway speed : 42 knots
 Wind : 100 knots

Power Supply and Consumption

DC input (isolated) : +10.8VDC to +31.2VDC
 Power (max) : 150W including antenna

Physical Data

Dimension : BDU : 360 x 250 x 67 mm
 : ADU : 653 (Dia) x 652 mm
 Weight : BDU : 3.9 Kg
 : ADU : 18.5 Kg

Primary Handset

Display : 2 in, 220 x 176 pixel TFT, 65K Color LCD
 Dimension : 142 x 56 x 22 mm
 Weight : 390g / 0.8 lbs
 Ingress Rating : IP66
 Operating Temperature : -20 to +55°C
 Storage Temperature : -30 to +70°C

Feature highlights of Primary Handset

- Configuration settings
- Basic circuit-switched telephone functions
- Phone book retrieval from SIM card
- Call log for most recent 5 missed, received and dialed calls with date and time stamps
- Short message service (SMS)
- User-friendly menu driven graphical user interface
- Supports Hands free headset
- Analog handset does not need SIP registration to BDU



Addvalue Innovation Pte Ltd. 8 Tai Seng Link, Level 5 (Wing 2), Singapore 534158.
 Tel: +65 6509 5700, Fax: +65 6509 5701, Website: www.addvaluetech.com

© 2016 Addvalue Innovation Pte Ltd. All rights reserved. Addvalue may have pending patent applications, trademarks or registered trademarks, copyrights, or other intellectual property rights covering subject matter in this document. The furnishing of this document does not give you any license to these intellectual properties. This material may contain unintended errors or omissions and is subject to change without notice. It is provided as is and without any express or implied warranties, including merchantability, fitness for a particular purpose and non-infringement. Addvalue shall not be liable for any special, indirect, incidental or consequential damages as a result of its use. Addvalue, the Addvalue Enabled logo, Wideye and the Wideye logo are either trademarks or registered trademarks of Addvalue Technologies Ltd and/or its affiliates in Singapore and/or other countries. Inmarsat, the Inmarsat logo registered trademarks of Inmarsat Global Limited in the United Kingdom and/or other countries, and are used by Addvalue Innovation Pte Ltd under license.